



## MZQE.EX16185 Fire Hose, Lined, Uncoupled, for Municipal and Industrial Use

[Page Bottom](#)

### Fire Hose, Lined, Uncoupled, for Municipal and Industrial Use


[See General Information for Fire Hose, Lined, Uncoupled, for Municipal and Industrial Use](#)**NEWAGE FIRE PROTECTION INDUSTRIES PVT LTD**

EX16185

4/7,  
Champaklal Udyog Bhavan  
Sion East  
Mumbai, 400022 INDIA

Model	Hose Size (in.)	Service Test Pressure (psig)	Hose Type	Ratings	Comments
NEWAGE PYROPROTECT PYROFLEX PERMALINE	1-1/2, 1-3/4, 2, 2-1/2	200	Single-jacketed	Ozone resistant	Lining (NBR/PVC) Jacket (Polyester filament yarn synthetic warp threads and polyamide filament filler threads) Cover (NBR/PVC)
NEWAGE PYROPROTECT PYROFLEX PERMALINE	3	150	Single-jacketed	Ozone resistant	Lining (NBR/PVC) Jacket (Polyester filament yarn synthetic warp threads and polyamide filament filler threads) Cover (NBR/PVC)
FYRFYTER NEWAGE PREMIER NEWAGE SUPREME NEWAGE FIRE MASTER SUPER NEWAGE COMMANDER SUPER NEWAGE FIRE CHIEF NEWAGE FIRE OUT RRL	1-1/2, 2-1/2	200	Single-jacketed	Ozone resistant	Lining (EPDM) Jacket (Woven polyester) Outer Coating ( Synthetic elastomer)

Trademark and/or Tradename: "NEWAGE PYROPROTECT", "PYROFLEX", "PERMALINE",



Last Updated on 2017-09-12

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".