

# **2217LED Specifications**

### **Unit Information**

Model #: 2217LED / Item #15460 UPC-IC (12 Digit): 016731154608

## **Master Pack Dimensions**

Weight: 9.9 lbs. (4.5 kg) Cube: 1.43 ft<sup>3</sup> (0.04 m<sup>3</sup>)

Quantity: 24

## **Specifications**

Power Source: 2x 'D' Cell Alkaline

Light Source: LED Life: 30,000 hrs Runtime: 200 hrs

Light Output: 50 Lumens Beam Distance: 88 Meters

Weight (Without batteries): 5.0 oz (.13 kg)

## **Unit Dimensions**

Length: 8.1 in. (20.6 cm) Width: 2.3 in. (5.8 cm) at head

#### **Safety Approvals**

UL Protection Methods Intrinsically Safe Divisions 1 & 2 Class I, II, III Div 1 Groups A-G Class I, II, III Div 2 Groups A-G Operating Temp T5

#### **Product Features**

- For use in hazardous atmospheres
- 'S' Biner included for quick attachment
- Waterproof, IP67 rating
- 'Switch Guard' Prevents accidental lighting
- Three-way switch : On-Momentary-Off
- Anti-roll tube
- Faceted reflector for more light



WorkSafe™ Model # 2217LED





