

## Manual Breakglass

- Available in flush or surface mounted models.
- Plastic film on glass.
- Test key inserted from bottom.
- Open circuit with series resistor.
- Suitable for the majority of conventional fire alarm system.
- \* Clear protection cover is also available. (S-330C)

<b>Model</b>	: S-330
Operating Contact	: 6A 125/250VAC
Resistance	: 30mΩ
Ambient Temperature	: -25°C~+85°C
Dimensions	: 88mm (H)×88mm (W)×52mm (D)
Weight	: About 165g



## Fire Indicating Lamp



AH-9719

<b>Model</b>	: AH-9719
Consumption	: 24 V DC 60 mA / LED 20 mA
Bulb	: 30V /2W white bulb or LED
Lamp Cover	: Glass or fire-proof plastic
Lamp Base	: Fire-proof plastic
Weight	: Glass : about 160g Fire-proof plastic
Dimensions	: 90mm(D) × 70mm(H)

## Resettable Manual Call Point



AH-0817

- Red LED with current limiting resistor.
- Three different resistance selectable (270, 470, 680 ohm).
- Choice of red, yellow, blue or green finish also available for custom-made.
- Clear protection cover is also available (optional).

<b>Model</b>	: AH-0817
Operating Contact	: 6A 125/250VAC
Resistance	: 30mΩ
Ambient Temperature	: -25°C~+85°C
Dimensions	: 87.5mm (H)×87.5mm (W)×54mm (D)
Weight	: About 145g

## Fire Alare Bell 6"

<b>Model</b>	: S-332
Voltage	: 24V DC
Current	: 25 mA
Sound Output	: 93db @ 1M
Movement	: Motor,Pinion and Striker
Movement Features	: DC motor,acetral gear wheel steel striker
Gong	: Steel,secured with phillips screw
Base Plate	: Molded black polycarbonate
Dimension / Weight	: 6 " (152 mm) / 0.85 kg



S-332