

Sectional Disconnects and Universal Sticks

Tested per OSHA & ASTM F711



Features & Applications

- Tested per OSHA & ASTM F711
- Non-conductive splices snap together for just the right job length
- Compact fittings interchange on orange Epoxiglas® insulated sections
- Easily store in limited space
- Rounded metal buttons and stainless-steel springs for long life
- Silicone coating and gloss finish seal out moisture
- Base cap included with top sections

Note: For SAFETYSHIELD™ Hot Stick Barrier to fit tools on this page, see page 2129.

Tree Trimmers



Standard Switch Head Disconnect
Non-Metallic Disconnect
Plastic Universal
1 1/4"-diameter Pole

Catalog Number	Length	Approx. Weight
Standard Switch Head Disconnect		
C4032073	6 inches	3/4 lb./0.34 kg.
C4032053	4 feet	2 3/8 lb./1.07 kg.
C4032054	6 feet	2 5/8 lb./1.18 kg.
C4032055	8 feet	2 7/8 lb./1.29 kg.

Catalog Number	Length	Approx. Weight
Non-Metallic Disconnect Head		
C4032095	6 inches	1 lb./0.45 kg.
C4032060	6 feet	2 1/2 lb./1.13 kg.
C4032061	8 feet	2 3/4 lb./1.22 kg.

Catalog Number	Length	Approx. Weight
Plastic Universal Head		
C4032071	6 inches	5/8 lb./0.28 kg.
C4032046	4 feet	2 lb./0.90 kg.
C4032047	6 feet	2 1/4 lb./1.01 kg.
C4032048	8 feet	2 1/2 lb./1.13 kg.

Catalog Number	Length	Approx. Weight
Tree Trimmer Head		
C4032096	*2 feet	3 1/4 lb./1.46 kg.
C4032097	*4 feet	3 1/2 lb./1.57 kg.

*Length excludes trimmer head fitting.

Catalog Number	Length	Approx. Weight
Extension Section		
C4032062	4 feet	2 lb./0.90 kg.
C4032063	6 feet	2 1/4 lb./1.01 kg.
C4032064	8 feet	2 1/2 lb./1.13 kg.
C4032133	10 feet	2 3/4 lb./1.22 kg.

Catalog Number	Length	Approx. Weight
Base Cap		
C4032069	5 inches	1/8 lb./0.06 kg.

